



BCS America Model 718 Two Wheel Tractor (821CR180)

[Read More](#)

SKU: 821CR180

Categories: [BCS America](#)

Product Description

BCS America Model 718 Two Wheel Tractor (821CR180)

Like the 710, the Model 718 is lightweight, compact in size, and loaded with BCS quality. It features the same all-gear-driven transmission and automotive clutch. And the 718 powers the same basic set of attachments.

Of course, there are differences between the two models; one of which is the engine. The 718 is powered by Honda's commercial GX200 engine.

The second difference is the handlebar system. From the base of the steering column to the operator controls, the handlebar system screams user-friendliness and versatility.

- **Stationary positioning** of the control rods eases wheel speed selection and PTO engagement.
- **Anti-vibration** buffers are used at the base of the steering column to minimize the transfer of vibration generated by the attachment to the hands of the operator.
- Seven vertical height position options are instantly available with the push of a lever. In combination with the three horizontal position options, the operator has easy access to **21 different handlebar positions!**

The last two features are particularly helpful when sickle bar mowing steep slopes, under semi-dwarf fruit trees, and under fencing. When climbing a slope, the handles need to be lowered; when descending, they need to be raised, and when mowing across the slope, they need to be offset so the operator can comfortably walk alongside on the downhill side of the mower and maintain a vertical posture.

FEATURES

- All Gear Drive w/ Heat-treated Steel Gears & Embedded Ball Bearings
- Double Cone Clutch
- Best Warranty in the Industry
- Limited Lifetime Transmission Warranty*
- 3-year Engine Warranty
- Convenient Shuttle-style Forward/Reverse Control

- Easily Adjusted Anti-Vibration Handlebars w/ 180° Rotation
- 7 Vertical Handlebar Settings (front & rear)
- 3 Horizontal Handlebar Settings (front & rear)
- Two Working Speeds in Each Direction
- Transport Speed (rear-mount only)

SPECS

- Engine: Honda GX200
 - Electric Start Option: No
 - Transmission: All Gear Drive
 - Clutch Type: Double Cone, Spring-Loaded Axle
 - Configuration: Straight Axle; Optional ratcheting hub accessory
 - Working Gears: 2 forward, 2 reverse
 - Working Gear Speeds: 1st gear: 0.6 mpg; 2nd gear: 1.4 mph
 - Transport Gear Speed: 6.8 mph (rear-mount mode only)
 - Standard Wheel/Tire Size: 4x8x16"; Optional sizes: 4x10x18" or 5x10x19.5"
 - Weight: 220 lbs (with 18" tiller); 242 lbs (with 20" tiller)
-