



## **BCS America Model 710 Two Wheel Tractor 821K0180**

[Read More](#)

SKU: 821K0180

Categories: [BCS America](#)

### **Product Description**

## **BCS America Model 710 Two Wheel Tractor 821K0180**

The 710 is lightweight, compact in size, and loaded with BCS quality. Designed for decades of dependable service, its all-gear driven transmission, automotive-style clutch, and powerful Kohler CH270 Command Pro engine make this a great investment for those interested in a basic range of attachments. Because the engine's power is not lost due to the inefficiency of belts, the tractor comfortably handles an 18" or 20" Rear-Tine Tiller, Hiller/Furrower, 30" or 40" Sickle Bar Mower, 24" Snow Thrower, Water Transfer Pump, and more.

In the family garden, the 710 with tiller is a superior, do-everything tool - bust sod, prepare seedbeds, power compost cover crops, create planting furrows, hill potatoes, and cultivate between rows to eliminate weeds! For the commercial market garden, the 710 is great for cultivating - no untilled strip in the center of the row and a maximum working speed of 1.4 miles per hour.

### **FEATURES**

- All Gear Drive w/ Heat-treated Steel Gears & Embedded Ball Bearings
- Double Cone Clutch
- Best Warranty in the Industry
- Limited Lifetime Transmission Warranty\*
- 3-year Engine Warranty
- Convenient Shuttle-style Forward/Reverse Control
- Easily Adjusted Handlebars w/ 180° Rotation
- 3 Vertical Handlebar Settings (rear); 4 Vertical Handlebar Settings (front)
- 3 Horizontal Handlebar Settings (front & rear)
- Two Working Speeds in Each Direction
- Transport Speed (rear-mount only)

### **SPECS**

- Engine: Kohler Command Pro CH270 with Quad-Clean heavy duty cyclonic air cleaner
  - Electric Start Option: No
  - Transmission: All Gear Drive
  - Clutch Type: Double Cone, Spring-Loaded
  - Axle Configuration: Straight Axle; Optional ratcheting hub accessory
  - Working Gears: 2 forward, 2 reverse
  - Working Gear Speeds: 0.6 mph & 1.4 mph
  - Transport Gear: Yes, 3rd Gear (rear-mount only)
  - Transport Gear Speed: 6.8 mph
  - Standard Wheel/Tire Size: 4x8x16"
  - Weight: 213 lbs (with 18" tiller); 235 lbs (with 20" tiller)
-